


A2-70/A4-80 Stainless Steel Hex Nut 304/316 不銹鋼絲母

A2-70 / A4-80

DIN 934

73122 (A2-70)

73133 (A4-80)



Order example: DIN 934 A4-80 M16 (Order Code: 73133.160.000)

Material Standard:	ISO 3506 Part 2:1997
Specification:	DIN 934
Material:	A2-70 / A4-80 Stainless Steel

d (diameter)	Thread Pitch	m (max.)	s (max.)	A2-70	A4-80	
M3	0.5	2.40	5.50	030000		1000
M4	0.7	3.20	7.00	040000		1000
M5	0.8	4.00	8.00	050000		1000
M6	1	5.00	10.00	060000	060000	1000
M8	1.25	6.50	13.00	080000	080000	1000
M10	1.5	8.00	17.00	100000	100000	500
M12	1.75	10.00	19.00	120000	120000	200
M16	2	13.00	24.00	160000	160000	100
M20	2.5	16.00	30.00	200000	200000	50
M24	3	19.00	36.00	240000	240000	50
M27	3	22.00	41.00		270000	25
M30	3.5	24.00	46.00		300000	15
M33	3.5	26.00	50.00		330000	10


A2/A4 Stainless Flat Washer 304/316 不銹平介子

A2 / A4

DIN 125A

73202 (A2-70)

73203 (A4-80)



Order example: DIN 125A A4 M16 (Order Code: 73203.160.000)

Material Standard:	BS 6105:1981
Specification:	DIN 125A / BS 4320:1968
Material:	A2 / A4 Stainless Steel

Form A	d1 (max.)	d1 (min.)	d2 (max.)	d2 min.	s (max.)	s (min.)	A2	A4	
M3	3.4	3.2	7	6.7	0.6	0.4	030000		
M4	4.5	4.3	9	8.7	0.9	0.7	040000		
M5	5.5	5.3	10	9.7	1.1	0.9	050000		
M6	6.7	6.4	12.5	12.1	1.8	1.4	060000	060000	2000
M8	8.7	8.4	17	16.6	1.8	1.4	080000	080000	1000
M10	10.9	10.5	21	20.5	2.2	1.8	100000	100000	500
M12	13.4	13.0	24	23.5	2.7	2.3	120000	120000	500
M16	17.4	17.0	30	29.5	3.3	2.7	160000	160000	200
M20	21.5	21	37	36.2	3.3	2.7	200000	200000	200
M24	25.5	25	44	43.2	4.3	3.7	240000	240000	100
M27	28.5	28	50	49.2	4.3	3.7		270000	100
M30	31.6	31	56	55.0	4.3	3.7		300000	50
M33		34	60		5			330000	50