

Helical hammer drill bit with SDS-max shank

QUADRO-X

Helical hammer drill bit SDS-max

- Slender drill head with 4 cutting edges arranged in X shape, enabling the Quadro-X to penetrate quickly into even the hardest concrete.
- Large-volume double-threaded flute for instant removal of drilling dust. With Vario pitch from 25 mm dia.

- Core reinforcement for full power transmission.
- Extremely fast, extremely durable
- No digging, no risk of breakage in reinforced concrete.
- Extremely smooth running. The substantial reduction of vibrations relieves the strain on both the operator and the power tool.
- Dimensionally accurate bore-holes.
- Vacuum brazing/tempering process.

Application:

- Suitable for hammer drills with SDS-max chucking and Hilti hammer drills.
- For concrete, masonry and natural stone.
- Plastic hanger (PP) with adhesive label and Euro-normed hole.



Ø mm	Total length mm	Working length mm	EAN number 401446	Order number	OU
12,0**	340	200	8018770	139653	01
12,0**	540	400*	8018787	139654	01
12,0**	690	550*	8018794	139655	01
12,0**	940	800*	8023323	142691	01
14,0**	340	200	8018800	139656	01
14,0**	540	400*	8018817	139657	01
14,0**	940	800*	8023330	142692	01
15,0**	340	200	8018824	139658	01
15,0**	540	400*	8018831	139659	01
16,0	340	200	8018848	139660	01
16,0	540	400*	8018855	139661	01
16,0	940	800*	8023347	142693	01
18,0	340	200	8018862	139662	01
18,0	540	400*	8018879	139663	01
18,0	940	800*	8023354	142694	01
20,0	320	200	8018886	139664	01
20,0	520	400*	8018893	139665	01
20,0	920	800*	8018909	139666	01
20,0**	1320	1200*	8033063	145312	01
22,0	320	200	8018916	139667	01
22,0	520	400*	8018923	139668	01
22,0	920	800*	8018930	139669	01
22,0**	1320	1200*	8033070	145313	01

* Pilot drill to at least 150 mm with a short drill bit of the same diameter.

** Standard drill with 2 cutting edges, single flute

Ø mm	Total length mm	Working length mm	EAN number 401446	Order number	OU
24,0	320	200	8018947	139670	01
24,0	520	400*	8018954	139671	01
25,0	320	200	8018961	139672	01
25,0	520	400*	8018978	139673	01
25,0	920	800*	8018985	139674	01
25,0**	1320	1200*	8033087	145314	01
28,0	370	250	8018992	139675	01
28,0	570	450*	8019005	139676	01
28,0	670	550*	8019012	139677	01
30,0	370	250	8019029	139678	01
30,0	570	450*	8019036	139679	01
32,0	370	250	8019043	139680	01
32,0	570	450*	8019050	139681	01
32,0	920	800*	8019067	139682	01
32,0**	1320	1200*	8033094	145315	01
35,0	370	250	8019074	139683	01
35,0	570	450*	8019081	139684	01
35,0	670	550*	8019098	139685	01
37,0	570	450*	8044977	209446	01
37,0	920	800*	8044984	209448	01
38,0	370	250	8019104	139686	01
38,0	570	450*	8019111	139687	01
40,0	370	250	8019128	139688	01
40,0	570	450*	8019135	139689	01
40,0	920	800*	8019142	139690	01
45,0	570	450*	8044991	209449	01
52,0	570	450*	8045004	209450	01

For chisels with SDS-max shank, please turn to Page A 21