


**JAM-S SLEEVE ANCHOR 鍍鋅輕磚拉爆**

ST ZP

01211



Application:

installing pipe bracket, trucking, cable tray and suspended ceilings. Light to medium metalwork, hand rails, signs and gates etc.

Material:

steel, zinc plated  $\geq 5\mu\text{m}$ 

Base Material:

concrete, brick, masonry and hollow brick (concrete 30 N/mm<sup>2</sup>)


Item No.	Description	Hole Diameter d0 (mm)	Thread Size x L (mm)	Min. Hole Depth hs (mm)	Tightening Torque Tinst (Nm)	Fixture Thickness tfix (mm)	Base Material Thickness (mm)	Tensile Load (kN)	Shear Load (kN)	
01211080040	S 8 x 40	8	M6 x 47	28	8	12	80	1.9	3.0	100
01211100050	S 10 x 50	10	M8 x 60	32	25	18	100	3.8	4.4	100
01211120060	S 12 x 60	12	M10 x 69	38	40	22	120	5.5	7.2	100
01211120075	S 12 x 75	12	M10 x 84	38	40	37	150	5.5	7.2	100

**JAM-S A2/A4 SLEEVE ANCHOR 304/316 不銹鋼輕磚拉爆**

A2 / A4

71212 (A2)

71213 (A4)



Material:

A2 / A4 Stainless Steel

Base Material:


concrete, brick, masonry and hollow brick (concrete 30 N/mm<sup>2</sup>)

Item No.	Description	Hole Diameter d0 (mm)	Thread Size x L (mm)	Min. Hole Depth hs (mm)	Tightening Torque Tinst (Nm)	Fixture Thickness tfix (mm)	Base Material Thickness (mm)	Tensile Load (kN)	Shear Load (kN)	
71212080040	S 8 x 40	8	M6 x 47	28	8	12	80	1.9	3.0	100
71212100050	S 10 x 50	10	M8 x 60	32	25	18	100	3.8	4.4	100
71212120060	S 12 x 60	12	M10 x 69	38	40	22	120	5.5	7.2	100

**JAM-SH BOLT HEAD SLEEVE ANCHOR 鍍鋅六角頭拉爆**

ST ZP

01221



Material:

steel, zinc plated  $\geq 5\mu\text{m}$ 

Base Material:

concrete, brick, masonry and hollow brick (concrete 30 N/mm<sup>2</sup>)

Item No.	Description	Hole Diameter d0 (mm)	Thread Size x L (mm)	Min. Hole Depth hs (mm)	Tightening Torque Tinst (Nm)	Fixture Thickness tfix (mm)	Base Material Thickness (mm)	Tensile Load (kN)	Shear Load (kN)	
01221080060	SH 8 x 60	8	M6 x 64	38	10	22	100	2.8	3.5	100
01221100060	SH 10 x 60	10	M8 x 66	44	25	16	120	4.0	4.8	100
01221120065	SH 12 x 65	12	M10 x 71	56	40	9	120	5.9	7.8	50
01221120080	SH 12 x 80	12	M10 x 86	56	40	24	150	5.9	7.8	50
01221120110	SH 12 x 110	12	M10 x 116	56	40	54	200	5.9	7.8	50
01221160110	SH 16 x 110	16	M12 x 116	55	70	55	200	8.3	9.5	50